

COMFORTWIDE™ SERIES

Low
Bed Frames



COMFORT WIDE™

Push-button slide technology with locking positions 35-39-42 inches wide



EVAC POSITION™

Pass through doors no matter the assist device attached

RETRACTABED® EX5000 MODEL

Clinical-Contour® – exclusive feature that reduces skin shear and the repositioning of residents

Evac Position™ - extra position to make the bed thinner so if a side bar is attached it can still pass through doors less than 42 inches wide

Comfort Wide™ – bed expands to 42 inches wide without the use of tools for more comfort and flexibility

Staff Lockout Control – standard feature to prevent unnecessary operation

Wall Bumpers - soft non-marking bumpers come standard to protect wall from damage

Retracting Bed Frame – reduces potential falls and increases staff productivity

Embedded Bed Controls – optional fixed controls in assist bar or head rail reduces replacement handsets and increases staff productivity

Steel Pivots - each pivot has hardened steel bushings or high bolts to extend the life of the bed



THE INNOVATIVE HEALTHCARE SOLUTION
Made in the U.S.A.

PHYSICAL SPECIFICATIONS

Deck Height Low.....	9"
Deck Height High.....	25"
Sleeping Surface.....	35"w, 39"w, 42"w x 80" l
Length Retracted.....	71"
Length Extended.....	85"
Maximum Safe Working Capacity.....	500 lbs
Product Weight.....	225 lbs
Maximum Back Angle.....	62°
Maximum Knee Angle.....	22°
Mobility Height.....	any height

COMFORTWIDE™ SERIES



Fall Risk
Non-Retractable Bed

Fall Prevention
Retractable Bed

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature.....	41° F to 104° F (5° C to 40° C)
Operating Relative Humidity.....	20% to 90% @ 86° F / 30° C
Operating Atmospheric Pressure.....	700 to 1600 hPa
Storage Temperature.....	-10° C to -50° C
Storage Relative Humidity.....	20% to 90% @ 86° F / 30° C
Storage Atmospheric Pressure.....	700 to 1060 hPa

ELECTRICAL SPECIFICATIONS


Main Voltage Input.....	120 V AC
Max Current Input.....	2.70 A
Main Frequency Input.....	60 Hz
Controller Output Voltage.....	24 V DC

LIMITED WARRANTY

15 years on bed frame mechanics
5 years on drive system
1 year on wood, casters & handsets
Lifetime warranty on all welds

Approvals: IEC60601-1:2005 2nd edition, ANSI / AAMI ES60601-1:2005 2nd edition, and CAN / CSA-22.2 No 60601-1:2008

ENDBOARD OPTIONS



ENGLISH OAK



MAHOGANY



CHERRY



LIGHT OAK

ACCESSORIES



4" Bed Extender



Pivoting Assist Bars



Battery Backup



Floor Bumper Guard



Pivoting Assist Bars with
Fixed Handset



Trapeze Assembly



Transport Dolly



1/4 Length Side Rail
with or without Fixed Handset



THE INNOVATIVE HEALTHCARE SOLUTION
Made in the U.S.A.